

QUANTUM

Series and features of the energy-efficient chiller series



auti

engie-refrigeration.de

For chilling: **QUANTUM**

It starts smoothly, then runs quietly and with low vibration. It features excellent energy efficiency and its oilfree system operates without any difficulties.

It is low maintenance and reliable. It sets standards in chiller technology: the **OUANTUM** from **ENGIE** Refrigeration.

After years of continuous development, the QUANTUM is now a chiller that provides an astonishingly broad range of services. The different series offer impressive solutions for each chilling situation and they can each be individually tailored to ensure that every customer gets exactly the refrigeration they need.

Our expert Service department supervises each QUANTUM chiller, from planning, through installation, operation and maintenance, to checking whether the chiller complies perfectly with requirements - or whether it needs to be adjusted. After all, genuinely energy-efficient refrigeration depends on two factors: a chiller from the QUANTUM product family and the technical expertise of the refrigeration specialists at ENGIE Refrigeration.

QUANTUM. Providing cooling.



However, it is not just QUANTUM's long-lasting refrigeration and its environmental credentials, with drastically reduced energy costs, that impress. It is also exceptionally easy to handle. It begins with a staggered start-up of the individual compressors, thereby resulting in low start-up currents, among other things. Then it switches over to quiet and lowvibration operation. QUANTUM's continuous power control eliminates inefficient pulsing behaviour in the compressors, ensuring highly constant temperatures. Result: The network of consumers does not experience negative temperature fluctuations and remains thermally stable; there is no need to take measures to regulate and store cold water.



Impressive performance: **QUANTUM**



Save operating costs:

- High-efficiency compressors > no friction losses thanks to magnetic bearings
- · Each compressor is fitted with a frequency converter > maximum efficiency during partial load
- Heat exchangers with high-performance ribbed pipes > optimum heat transfer with minimum pressure loss
- Minimum overheating of refrigerant

It is the underlying concept of an oil-free compressor and contact-free magnetic bearings that make QUANTUM so powerful and efficient. There is no material wear, significantly lower maintenance costs and all the regulations and precautionary measures associated with oil operation simply do not apply. Another advantage of oil-free operation is the more efficient heat transfer (in the condenser and the evaporator), which is not impaired by oil. This increases efficiency and helps to save on operating costs.

DUANTUM. Built for efficiency.

What's in every QUANTUM

erals in the

cold water

network

positioning Low operating

costs

 High level of operational reliability and safety on site

Turbo compressor	Oil-free system	Frequency converter on every compressor	Open-Flash- Economizer	Multiple compres- sor design (up to 8 parallel)	Flooded tube bun- dle evapo- rator	Durable, high-quali- ty fittings and sen- sors	Start-up current of compres- sors under 5 amp	Control with PLC	EN B
The compressor design enables a high full load and part load EER. The turbo machine operates with minimum internal losses. This results in excellent energy efficiency.	As no compo- nents are re- quired for oil return, there are fewer malfunc- tions and/or leaks – and any leaks that do occur do not in- volve flammable oil, which is also hazardous to the groundwater. There is no need for oil changes. The EER is in- creased because the heat transfer in the refrigera- tion circuit is not impaired by oil.	Particularly effi- cient during part load thanks to continuous power control. In gener- al: the QUANTUM controller has an impressively high quality of control.	Built-in Open- Flash-Economizers ensure high EER values. They opti- mise the entire re- frigeration process without increasing the machine's space require- ments.	Better to be safe: other compres- sors take over in case of failure. The redundant design also makes it possible to replace a com- pressor during live operation.	Low temperatures difference be- tween the chilled medium and re- frigerant improve efficiency. High- performance ribbed tubes for optimum heat transfer during evaporation result in low tempera- ture differences between the re- frigerant and the chilled medium. The design of the condenser allows minimal refriger- ant overheating. These two effects are what make QUANTUM so effi- cient.	Built to last: the excellent quality of all compo- nents guarantees a low susceptibil- ity to errors or failures. It is also easy and effi- cient to replace a component.	When a compressor starts up, there are none of the dreaded current peaks. In addi- tion, a staggered start-up is possi- ble.	It all depends on the setting: PLC offers more con- trol and regula- tion possibilities than standard solutions and sets a high level industry stand- ard.	Cor EM on net ity 610 DIN 6-4
 Low operating costs Low noise emissions Low vibration 	Clear, compact machine design because no complex com- ponents are needed for oil return Low space requirement Simple	 Low operating costs Low investment costs in system periphery Steady chilled medium temperature Fewer periph- 	 Low operating costs Small machine footprint 	 High level of operational reliability 	 Low operating costs Clear, compact machine design Low pressure loss on chilled medium side 	 Low maintenance and servicing costs High level of operational reliability 	 Stable electrical mains supply Low connected power output needed 	 Adaptation to individual cus- tomer require- ments High level of operational reliability 	F e ii t v r i i

equipment

MC class

Protection class IP54

mplies with IC guidelines electromagtic compatibil-DIN EN 000-6-2 and N EN 61000-

For secure refrigeration: QUANTUM machines have protection against physical contact and protection against spray water.

Large range of electrical options

Each QUANTUM can be equipped with a variety of options to customise it. These include surge protection, integration of pump performance parts, a universal measuring device, a remote access option and various BUS connections.

ligh level of electromagnetc compatibility n public distrioution netvorks Avoidance of malfunctions n electrical

 High level of operational reliability

- Adaptation to individual customer requirements
- Easy to integrate in existing refrigeration systems



QUANTUM X

Packs a lot into its small frame: the **OUANTUM X is** compact and has a variety of uses.

For dry and wet cooling, for heat recovery or even as a heat pump, this allrounder operates reliably and efficiently in a capacity range of 300 to 3,000 kW.

Thanks to the twin tubed condenser technology, simultaneous refrigeration and heat utilisation are possible, e.g. for heating buildings or pre-warming the hot water system. Unused waste heat can be transferred out through a separate re-cooling circuit.

If the QUANTUM is used as a heat pump, it is controlled in accordance with the desired heating medium temperature.

QUANTUM X. The all-rounder with a broad range of uses.

The QUANTUM X profile

- Water-cooled compact machine for installation in a machine room
- Capacity range 300-3,000 kW with high re-cooling temperatures
- Flexible application: > Dry or wet cooling
- > Heat recovery
- > Heat pump
- > Optionally with R-513A or R-134a

> Optional refrigerant: R-513A or R-134a

Green. sustainable. efficient: QUANTUM G uses the environmentally friendly refrigerant R-1234ze with a GWP value (Global Warming Potential) of less than 1.

Sustainability is a legal requirement: the new Fluorinated Gases Ordinance from the EU prescribes a reduction in the use of environmentally harmful gases. One solution: the latest generation of the synthetic refrigerant (HFO).

QUANTUM G uses R-1234ze as a refrigerant, which persists just 18 days in the Earth's atmosphere and achieves an impressively low GWP value of less than 1.

By the way: QUANTUM G also proves with ease that environmental friendliness does not need to come at the expense of performance. Like the QUANTUM X, it takes up little space and has a wide variety of uses, with a capacity range of 200 to 3,000 kW.

OUANTUM G. Green refrigeration with a sustainable refrigerant.



QUANTUM G

The QUANTUM G profile

- Water-cooled compact machine for installation in a machine room
- Capacity range 200 3,000 kW with high re-cooling temperatures, sustainable and environmentally friendly:
- > Very small ecological footprint
- > Refrigerant R-1234ze with GWP < 1</p>

Water-cooled QUANTUM in the G-series with 1.2 MW refrigeration capacity



QUANTUM W

Can we do even better? This is a question that the refrigeration experts at ENGIE Refrigeration ask themselves all the time.

And with the QUANTUM W, they've provided an impressive answer: Yes, they can - once again, efficiency has been increased. Turbo compressors with frequency converter, Open-Flash-Economizers and the completely oilfree machine design are key components of this improvement. Although

the operating range is smaller than with the QUANTUM X, the refrigeration capacity and energy efficiency are better. The overall improvement in efficiency under full and part load plays an important role in ensuring that operating costs are reduced to a minimum, when calculated over the machine's service life. A QUANTUM W always provides maximum full load and part load EER values, and the ratio between the power input (electricity consumption) and power output (refrigeration capacity) is excellent.

QUANTUM W. The efficient machine for minimal operating costs.

The QUANTUM W profile

- Water-cooled compact machine for installation in a machine room
- Capacity range of 400-4,500 kW with low re-cooling temperatures Reduces operating costs:
- > Efficient in full and part load
- > Highest ESEER value
- > Maximum full load and part load EER
- > Optionally with R-513A or R-134a

> Optional refrigerant: R-513A or R-134a

If no cooling water is available, a QUANTUM can also be operated with air.

The QUANTUM A is air-cooled, has a capacity range of 300 to 1,800 kW, and is a refrigeration solution for outside installation. Its quiet running characteristics also fulfil strict requirements for low-noise operation.

Like all machines in the product family, the QUANTUM A is also produced using

as few components as possible, in an exceptionally high quality. Long-lasting fittings and sensors ensure secure operation and significantly reduce maintenance and servicing costs in the long run.

Options such as compressor soundreducing capsules and low-noise fans ensure quiet operation. Other options help ensure safe installation in any weather conditions, e.g. down to -20 °C.

OUANTUM A. Compact refrigeration with no compromises.



QUANTUM A

The QUANTUM A profile

- Air-cooled compact machine for outside installation
- Capacity range of 300–1,800 kW
- Space-saving refrigeration solution:
- > No re-cooling system necessary
- > No heating medium circuit necessary
- > No machine room necessary
- > Optionally with R-513A or R-134a



QUANTUM GA

Airy and green: The QUANTUM GA combines the benefits of QUANTUM G and QUANTUM A in a single machine.

With air cooling, it has a capacity range of 300 to 1,400 kW. It is filled with the environmentally friendly refrigerant R-1234ze, with a GWP of less than 1. Sustainable refrigeration solutions not only comply with the new Fluorinated Gases Ordinance of the EU, making them a future-proof investment, they also improve a company's image. After all, more and more consumers want to know how the products, goods and services they buy are made.

QUANTUM GA. Sustainable chilling in compact packaging.

The QUANTUM GA profile

- Air-cooled compact machine for outside installation
- Capacity range or 300-1,400 kW
 Sustainable and environmentally
- compatible:
- > Very small ecological footprint> Refrigerant R-1234ze with GWP < 1
- Compact refrigeration solution:
- No re-cooling system necessary
 - No heating medium circuit necessary
 - No machine room necessary
 - No machine room necessary

QUANTUM GS

Adapts to any space and provides lasting chilling.

The QUANTUM GS is a variant of the QUANTUM S that is operated with the environmentally friendly refrigerant R-1234ze. Like its bigger brother, the QUANTUM GS can be split, when necessary, into a machine unit for indoors installation and a re-cooling system for installation outdoors. It covers a capacity range of 300 to 2,000 kW. The separately positioned condenser is charged directly with refrigerant. The QUANTUM GS does not need any pumps for recooling.

QUANTUM GS. Tailored refrigeration.

The QUANTUM GS profile

- Machine unit inside + condenser
 outside
- Capacity range of 300-2,000 kW
- Air-cooled
- Efficient overall system, 100% adapted to customer requirements
- Sustainable and environmentally compatible:
 - Meets all current environmental requirements
- > Very small ecological footprint
- > Refrigerant R-1234ze with GWP < 1</p>



QUANTUM S

At ENGIE Refrigeration, we are focussed on refrigeration solutions.

A QUANTUM S is used where re-cooling has to be implemented with air and it is not possible to set up an air-cooled compact machine (e.g. due to limited roof loads, for aesthetic reasons or due to corrosive ambient air).

The QUANTUM S can be used, for example, if condensation heat is used to heat up the inlet air for a clean air system.

Focussing individually on the requirements and needs of the customer, the refrigeration experts at ENGIE Refrigeration created the split QUANTUM S to provide efficient overall systems with a capacity range of 300 to 2,800 kW.

QUANTUM S. The separable machine for all-round refrigeration solutions.

The QUANTUM S profile

- Machine unit inside + condenser outside
- Capacity range of 300-2,800 kW
- Air-cooled
- Efficient overall system, 100% adapted to customer requirements
- Optionally with R-513A or R-134a

Optional refrigerant: R-513A or R-134a

QUANTUM MARENUM





Water-cooled QUANTUM in the MARENUM series, with three compressors

In its element when things get stormy.

The QUANTUM MARENUM is seaworthy and available in many variants, tailored to individual applications: for ferries, freighters or yachts, and even for use on non-civil ships. Because recooling on ships frequently involves the direct use of salty sea water, the QUANTUM MARENUM is especially corrosion-resistant and resilient. It is also stable: thanks to special shock absorbers, the chiller "withstands" acceleration and rough seas.

It is of course water-cooled, and the QUANTUM MARENUM's refrigeration capacity starts at 300 kW – everything beyond that (capacity range, efficiency, electrics, heating medium) is adapted to the requirements of civil and non-civil shipping.

QUANTUM MARENUM. The stable chiller for use at sea.

The QUANTUM MARENUM profile

- Compact machine for inside installation
- Capacity range from 300 kW
- Water-cooled (including salt water)
- Specially adapted to maritime requirements, civil and non-civil
- Seaworthy
- Top material guality (e.g. non-rusting steels)
- Redundant compressors for system stability
- Compact construction for high refrigeration power with a small footprint
- Optionally with R-513A or R-134a

Optional refrigerant: R-513A or R-134a

It packs a punch.

The QUANTUM P provides a refrigeration capacity of up to 10,000 kW and is therefore especially suitable for use in district cooling networks. In this kind of network, multiple consumers are supplied through a pipeline system with refrigeration that is generated in a refrigeration centre. At the consumer's site, all that is normally installed is a transfer station. This is a highly efficient, spacesaving and flexible way to generate and distribute refrigeration. To sum it up: it's forward-looking!

In a large dimensioning in the megawatt range, the QUANTUM P clearly demonstrates its energy efficiency when generating refrigeration, and operators can benefit from significantly lower energy costs, or pass these benefits on to end consumers. Another benefit for the end consumer: a district cooling network is continuously monitored, ensuring a constant supply of refrigeration.

QUANTUM P. The power pack at the heart of district cooling networks.

QUANTUM P

The QUANTUM P profile

- Water-cooled compact machine for inside installation
- Capacity range of 4,500-10,000 kW
- Highly efficient in full and part load
- 100% adapted to customer requirements
- Powerful and suitable for use in district cooling networks
- Optionally with R-513A or R-134a

> Optional refrigerant: R-513A or R-134a

ENGLE Refrigeration – efficient refrigeration, designed in Germany made in Germany.

We have been operating under our new brand name since 2016 and we have a new, modern headquarters - meaning we are better positioned than ever to put our expertise into practice.



Excellent refrigeration technology know-how



Comprehensive service. tailored to individual require-



Selection of the best components



An efficient refrigeration solution that is 100% tailored to you



ENGIE Refrigeration. The home of refrigeration.

ER.Q.EN.01.19

ENGLE Refrigeration supplies the right cooling for every process: from efficient chillers, environmentally friendly heat pumps and modular re-cooling systems to turnkey solutions such as refrigeration containers or modules. Efficiency, sustainability, cost effectiveness and first-class expertise in technical solutions are hallmarks of every ENGLE Refrigeration project. Our individualised advice and comprehensive services are centred around our customers and their requirements. As a member of the worldwide ENGLE Group, we have a global network of specialists at our disposal and can realise our refrigeration solutions both at home and abroad.

ENGIE Refrigeration GmbH

Josephine-Hirner-Strasse 1&3 D-88131 Lindau T + 49 8382 706-1 F + 49 8382 706-410 refrigeration@de.engie.com engie-refrigeration.de

Sales International

sales.refrigeration@de.engie.com

Service International

service.international@de.engie.com

© 2019 ENGIE Refrigeration GmbH

